



3rd International Workshop on Beam Orbit Stabilization - IWBS2004
December 6-10, 2004

Hotel Kirchbühl, Grindelwald, SWITZERLAND

Orbit Stabilization at Taiwan Light Source


Kuo-Tung Hsu

December 6, 2004

NSRRC



NSRRC Accelerator



Major Parameters of the Storage Ring

Lattice type	Combined function Triple Bend Achromat (TBA)
Operational energy	1.5 GeV
Circumference	120 m
RF frequency	499.654 MHz
Harmonic number	200
Natural beam emittance	25.6 nm-rad
Natural energy spread	0.075%
Momentum compaction factor	0.00678
Damping time	
Horizontal	6.959 ms
Vertical	9.372 ms
Longitudinal	5.668 ms
Betatron tunes horizontal/vertical	7.18/4.13
Natural chromaticities	
Horizontal	-15.292
Vertical	-7.868
Synchrotron tune	1.06×10^{-2} (SRF, 1.52×10^{-2})
Bunch length	9.2 mm (Doris Cavities, 800 kV) 6.5 mm (SRF, 1.6 MV)
Radiation loss per turn (dipole)	128 keV
Nominal stored current (multibunch)	200 mA (~2004), 300~400 mA (2005~)
Number of stored electrons (multibunch)	5×10^{11} (SRF cavity, 10^{12})



National Synchrotron Radiation Research Center

Efforts to Improve Beam Stability

Coupled-bunch instability :

RF gap voltage modulation (~ October 2004)

Superconducting RF (December 2004 ~)

(to accompany double the stored beam current).

Coupled bunch feedback system

Orbital stability:

Source Elimination

Ambient temperature, Water temperature, Enhance data acquisition system, Vibration elimination, Power quality improvement , Power supply improvement ...etc.

Orbit feedback system

Top-up injection



National Synchrotron Radiation Research Center

Mechanical Related Source Elimination


Program initiation	1997	1998	1999	2000	2001	2002	
Performance, T orbit lo/lo	> 1 (drift>50 m) >1%	~ 0.25	< 0.2 (drift~20 m)	~ 0.15 <3 m rms ~0.5%	< 0.1 (drift<5 m)	< 0.1 <1 m rms <0.3%	(2003) ~0.06%
1. Utility Capacity Improvement	CTW, CHW Stability		Utility building #2 construction CHW capacity improved				
2. Heat Source Stabilization	Global effect studies (air/water temp., cable heat)	Injector energy upgrade full energy injection	EPU air temp. Power supply heating	U5 air temp.			
3. Thermal-Mechanical Effects	Girder, thermal insulator, vacuum chamber, SR heat mask BL-, RF-DIW temp., I monitor						
4. Vibration	AHU, crane vibration pre-reduced	Damping study	Floor meas.	Piping improv.			
5. Sensors Implementation	Air temp. sensors	Position sensors	SCADA implementation electrical sensors				
6. Control System	Water control system upgrade VF controller implementation	Utility data archive system	AHU controller upgrade AHUs reorganized				



National Synchrotron Radiation Research Center

(J. R. Chen, et. al.)

Magnet (Water Temperature)



Caused by the temperature fluctuations of magnet cooling water

Magnet deformed ~ 10 μ m

Induced beam orbit drift: 5 ~ 50 μ m



Current status

Cooling water temp.: ~ 0.1



National Synchrotron Radiation Research Center



Girder Displacement



- Main cause: air temperature
Sensitivity to air temp.: $\sim 10 \text{ m} / \text{m} / \text{C}$
Induced beam orbit drift: 20-100 $\text{m} / \text{m} / \text{C}$
- Current status: $< 0.1 \text{ m}$ per 8 hr shift
Air temp. : $< 0.1 \text{ C}$
(utility control system improved)
Thermal insulator jacket




Expansion of Vacuum Chamber



- Caused by synchrotron light irradiation.
Sensitivity to water temp.: $\sim 10 \text{ m} / \text{m} / \text{C}$
Move the girder ($\sim 0.3 \text{ m} / \text{m} / \text{C}$) and BPM ($\sim 1 \text{ m} / \text{m} / \text{C}$)
Induced beam orbit drift: $\sim 10\text{-}30 \text{ m} / \text{m} / \text{C}$
- Current status
Vacuum cooling water temp.: $\sim 0.5 \text{ C}$

Power Supply Related High Frequency Orbital Noise (Source Elimination)




National Synchrotron Radiation Research Center

@ 136 mA (August 22, 2001)

High Frequency Corrector Power Supply Noise


Typical Corrector Spectrum




National Synchrotron Radiation Research Center

(K.B. Liu et al.)


Observation at Infrared Beamline



Environment of BPM System



Orbit Feedback System Architecture



Orbit Feedback System Summary

- * 22 correctors + 30 BPMs for both plane
- * Using measured response matrix
- * Singular Value Decomposition (SVD) approach to invert the response matrix
- * Proportional, Integral and Derivative (PID) control algorithm
- * Orbit acquisition rate 1 kHz
- * Loop bandwidth is about 5 Hz now (30 Hz before December 2003)
- * Unified system for global feedback and local feedback system
- * Remote enable/disable of the feedback loop
- * Orbit excursion reduced to less than $\sim \mu\text{m}$ level for ID operation
 - U5, U9 and EPU5.6
- * Suppress orbit leakage due to non-ideal dynamic local bump
 - EPBM
- * Prototype local feedback loop by using e-BPMs

Orbit Feedback System Summary (cont.)

- * DSP feedback engine was replaced by general purpose PPC module
 - User friendly development environment
 - Lift maintenance difficults
 - Slightly increase jitter < 50 μ sec (DSP < 10 μ sec)
- * Robustness enhancement of the feedback loop
 - BPM Check
 - RMS, data change rate, ...etc
 - Limited correct setting range



National Synchrotron Radiation Research Center

Problems and Plan of the Orbit Feedback System

Major Problems :

- * Loop bandwidth is too small right now
 - => cannot eliminate mechanical related oscillation
 - => Limited gap/phase changing speed of IDs

Short-term Plans:

- * Increase sampling rate o 2 kHz to 4 kHz
- * Modify corrector power supply regulation loop
- * Increase loop bandwidth > 100 Hz



National Synchrotron Radiation Research Center

Closed Orbit and Orbit Stability



Closed Orbit : ~10 μm rms with DC correction schemes.
(Peace Chang et al.)

Orbit distortions: < 10 μm rms during insertion gap scan
can be compensated for using look-up correction tables.
(Peace Chang et al.)


Beam orbit stability: a few μm level (peak-to-peak) with a
global feedback system. (C. H. Kuo et al.)



Eliminated Orbit Leakage for EPBM Operation



EPBM flip bump without feedback



* EPBM dynamic bump with feedback



(C.H. Kuo et. al.)

Insertion Devices in the TLS Storage Ring


Insertion Device	SWLS	EPU5.6	U5	SW6	W20	U9	IASW
Location Section	S1	S2	S3	S4/RF	S5	S6	Arc 2,4,6
Type	SC	Pure	Hyb.	SC	Hyb.	Hyb.	SC
Magnet Length (M)	0.835	3.9	3.9	1.404	3.0	4.5	0.85
Period Length (cm)	25	5.6	5	6	20	9	6
(Min.) Gap (mm)	55	18	18	18	22	18	18.5
Number of Periods	1.5	66	76	16	13	48	7.5
Maximum By (Bx) Field (Tesla)	6	0.67 (0.45)	0.64	3.2	1.8	1.25	3.5
Photon Energy (eV) [Used Range]	Min.	4000	80	5000	800	5	5000
	Max.	38000	1400	1500	14000	15000	14000
Deflection Parameter Ky (Kx)	190.5	3.52 (2.37)	2.99	17.9	33	10.46	19.6
Vertical Tune Shift (Horizontal Tune Shift)	0.0504 (-0.014)	0.011 (-0.012)	0.008	0.036	0.036	0.033	0.05
Installation Date	Apr. 2002	Sep. 1999	Mar. 1997	Dec. 2003	Dec. 1994	Apr. 1999	2005

without
Feed-forward
Tune
Correction

with
Feed-forward
Tune
Correction




National Synchrotron Radiation Research Center



The photon flux vs. photon energy of bending magnets and IDs at TLS. Two Taiwan beamlines, SP8-BM and SP8-U3.2, at Spring 8 are also depicted

Orbit stability of the NSRRC Storage Ring




With the follow-gap look-up table and global orbit feedback system, the orbit drift of the field scan of U5, U9 and EPU5.6 can be reduced from a few hundred microns to *a few microns*. When the gaps of U5, U9 and EPU5.6 are scanned from 19, 21, and 21 mm to 39, 41, and 41 mm, the closed orbit distortions indicated by the R4BPM5X (blue) and R3BPM3Y (green), those are used in the faster orbit feedback system, are within 2 microns in both horizontal and vertical planes.



National Synchrotron Radiation Research Center

(Peace Chang, et. al.)


Photon Beam Stability Monitor ($\Delta I_0 / I_0$)



National Synchrotron Radiation Research Center

Signpost of overall beam stability from users' viewpoints

History of the Photon Beam Stability ($\Delta I_0 / I_0$)




National Synchrotron Radiation Research Center

(K.K. Lin et. al.)


Top-up Injection Project

Top-up injection scheme planned.
Feasibility demonstrated.




(G.H. Luo et. al.)

Experiment of Top-up injection



(G.H. Luo et. al.)

Cooling Water and Chamber Temperature



National Synchrotron Radiation Research Center


(G.H. Luo et. al.)

Compound Displacement of the of Beam Position Monitor Reading

- Intensity dependency of BPM electronic and BPM support fixtures ($\sim \mu\text{m}$)
- Filling pattern dependency of BPM electronics ($\sim \mu\text{m}$)
- RF gap voltage condition variation
- BPM support structure ($\sim 10 \mu\text{m}$)
- Thermal related ($\sim 10 \mu\text{m}$)

$\delta x \sim 15 \mu\text{m}$

$\delta y \sim 5 \mu\text{m}$




National Synchrotron Radiation Research Center


(G.H. Luo et. al.)

Vertical Beam Position Variation


R1BPM1Y



R2BPM7Y




R6BPM4Y




Horizontal Beam Position Variation


R1BPM1X



R3BPM8X



R4BPM3X



Top-up Injection Plan

Renew 1.5 μ sec half-sine injection kicker to reduced jitter and to improve waveform matching .

Gate of the orbit feedback loop is a provincial solution to remedy mismatching problem of the injection kickers.

User experiment with injection gate and without is performed, acceptable results get up to now.

Improve gun pulser and linac performance to improve filling pattern control.

Studies of the injector reliability, injection efficiency, and minimization of orbit perturbation during injection, etc., are ongoing.

Top-up operation is scheduled in late 2005.



National Synchrotron Radiation Research Center

Parameters of the Proposed Taiwan Photon Source

Electron Energy	3 ~ 3.3 GeV
Current	400 mA at 3 GeV or 300 mA at 3.2 GeV (Top-up injection)
SR Circumference	518.4 m (h = 864 = 2 ⁵ ·3 ³ , dia.= 165.0 m)
BR Circumference	499.2 m (h = 832 = 2 ⁶ ·13, dia.= 158.9 m)
Lattice	24-cell DBA
Straight-section	10.5 m x 6 ($v_v = 10.5$ m, $v_h = 160$ m) 6 m x 18 ($v_v = 8$ m, $v_h = 110$ m) 3 m x 12 ($v_v = 4.5$ m, $v_h = 250$ m; In-achromat)
Bending-section	x 12
Emittance	< 2 nm·rad at 3 GeV (Distributed dispersion)
Coupling	1 %
RF Frequency	500 MHz
RF Max. Voltage	4.8 MV (4 SRF cavities)
RF Max. Power	720 kW (4 SRF cavities)
Site	NSRRC in Hsinchu Science Park , Taiwan
Building	223 m OD (700 m circumference) 139 m ID (437 m circumference)

Sub- μ m orbital performance is one of a design goal.



National Synchrotron Radiation Research Center

Summary

- * To achieve μm (sub- μm) orbital performance is a short term goal at TLS.
- * Further develop of fast orbit feedback system is needed in following area:
 - Corrector PS improvement
 - High sampling rate ($\sim 2 \text{ KHz}/4 \text{ KHz}$)
 - PS control interface
 - BPM system improvement in engineering as well as software functionality.
- * Top-up operation mode is scheduled, beam orbit stability will be improve further.
- * Sub- μm orbital performance is one of a challenge for the newly proposed 3 ~ 3.3 GeV Taiwan Photon Source



Thank you for you attention

